

Our Values















Energy Sphynx

Vessel Info

Full specification overleaf

Energy Sphynx is a light construction vessel capable working up to 3,000m water depth, with main 150t offshore crane.

- · Length 97m x breadth 22m
- Main deck 1,100m2
- 150t main offshore crane

- DP2 Class vessel
- Accommodation for 96 persons
- 2x WROVs

Fast Facts

- · Capable of working in water depth up to 3,000m.
- 2x WROV systems installed in purpose built enclosed hangar P/Stbd.
- Main deck area of 1,100m², forward area with minimum 10t/m² load and aft of 25t/m².
- · Special purpose ship (SPS) compliant.



subsea 7

General Information

Type Construction/Flexlay Classification DNV; 1A1 Offshore service vessel(+) BIS BWM(T) Clean(Design, Tier III) COMF(C-3, V-3) DK(+) DYNPOS(AUTR, E) E0 ECA(SOx-A) Ice(C), NAUT(OSV(A)) Recyclable SF SPS Builder **Qingdao Wuchuan Heavy Industry** Co., Ltd

2021

Registry (NIS)

Norwegian International Ship

Principal Dimensions

Flag/Port of registry

Length Overall (m) 97.149m Breadth Moulded 22.031m 7,388t Gross tonnage Net tonnage 2,217t Draft 7.20m Air draft 40.2m (from keel) Deadweight 5,331t

Main Deck

Year Built

1,100m² Deck Cargo Area **Deck Measurements** 45m x 21m **Deck Cargo Capacity** #3: 25 t/m2, #3 - #72: 10t/m2

Tank Capacities (100%)

Marine Gas Oil (m3) 1,263m³ Ballast 4,506m³ 1,147m³ Fresh potable water Misc.tanks 220m³

Power and Propulsion

Main engine 4x HIMSEN. Type: 6H32/40. 2,880Kw, 720rpm each 4x Siemens 3,360kVA (2,688kW) Generators Propulsion thrusters 2x, SCHOTTEL Azimuth each 3,000kW. Bow thrusters 2x SHOTTEL STT 7 FP, 2,050kW each Bow azimuth thruster 1x SCHOTTEL SRP 1012 ZSV FP,

1,000kW Stern thruster 1x SCHOTTEL STT 4 FP, 1,200kW

Vessel Speeds and Fuel Consumption

Maximum Speed 14.5 knots **Economic Speed** 10.0 knots **Economic Speed Fuel** Consumption 13m³/day

Cranes

AHC Deck Crane (main) 150t at 11m, 25t at 35m, water depth 3,000 single fall mode, AHC Auxiliary Offshore crane 25Te, 10t at 36m, water depth 650m, 2,200m of wire available

DP Systems

Kongsberg K-Pos 1x HiPAP 501, 1x USBL acoustic (Sonardyne Ranger 2), DPS 232, DPS132 1x RADius 1000Q 1x SpotTrack Sensors 4x Gyro **4x Motion Reference Units 4x Wind Sensors**

ROV

WROV 2x Quantum systems (200BHP) installed in vessel hangar P/STBD, rated for 2,500m water depth

Helideck

Type certified CAP437 20.9m x 20.9m (Suitable for S-92)

Accommodation

| Persons | 96 |
|---------------------------|----|
| Single cabins | 26 |
| Double cabins | 33 |
| Quadruple cabins | 1 |
| Office | 8 |
| Hospital | 1 |
| Conference/operation room | 1 |
| Gym | 1 |











