

Our Values



















## Vessel Info

Full specification overleaf

Siem Stingray is designed for subsea operation duties such as construction and installation work, inspection, and maintenance.

- · Length 120.8m x breadth 23m
- Main deck 1,300m<sup>2</sup>
- 250t AHC offshore crane

- DNV Class vessel
- Accommodation for 110 persons
- 2x WROVs

## **Fast Facts**

- Vessel build to ICE C class.
- Capable of working in water depth up to 3,000m.
- 2x WROV systems, 2x LARS (1 Over the side and 1 moonpool).
- Main deck area of 1,300m<sup>2</sup>, deck strength 10t/m<sup>2</sup>, deck max load 3,000t.
- Low fuel consumption through its diesel electric machinery and hybrid battery system.



# subsea 7

#### General Information

Type Construction/Flexlay Classification STX OSCV 03, 1A1 BIS Battery(Power) Clean(Design) COMF(C-3, V-3) Crane DK(+) DYNPOS(AUTR) E0 HELDK(S, H) Ice(C) NAUT(AW) Recyclable SF SPS Year Built 2014

**Bahamas** 

### Flag/Port of registry **Principal Dimensions**

Length Overall (m) 120.8m **Breadth Moulded** 23m Gross tonnage 8.878t Net tonnage 2,664t

### Main Deck

Deck Cargo Area 1.300m<sup>2</sup> 3.,000t Deck Load max Deck Strength 10t/m<sup>2</sup>

#### Tank Capacities (100%)

Fuel Oil (m3) 1,643m<sup>3</sup> Ballast 5,393m<sup>3</sup> Fresh water 1.009m<sup>3</sup> MEG 310m<sup>3</sup>

#### Power and Propulsion

Bow azimuth thruster

4x 2,880kW, Wartsila W6L32D Main engines 720rpm each 970kW, Cummins KTA38 Aux engines Propulsion thrusters 2x 3,000kW, KM Contaz 25 Bow tunnel thrusters 2x 1.900kW, KM TT2650 CP

#### Vessel Speeds and Fuel Consumption

Maximum Speed 12 knots **Economic Speed** 8 knots **Economic Speed Fuel** Consumption 12m<sup>3</sup>/day

#### **AHC Crane**

Main Line Single Fall 250t at 9m, 82t at 36m, water depth 3,000m Auxiliary Line Single Fall 20t at 40m, water depth 3,000m Approved for person riding

#### **DP Systems**

2x DGPS, DPS 132/232, Cyscan, RADius, 2x HiPAP 501, 3x Gyro, 3x Wind Sensors, 3x VRS

#### **ROV**

2x work-class ROV's rated to 3,000m 2x LARS (1 Over the side and 1 moonpool) witch active heave compensated umbilical winches

#### Helideck

Type certified CAP437 20.88m dia, maximum take of weight 15t

#### Accommodation

Persons 110















1,500kW, KM Vros TCNS 92