















Seven Seas

Vessel Info

Full specification overleaf

Seven Seas is a construction / flex-lay vessel capable of operating in water depths up to 3,000m.

- Length 153.24m x breadth 28.4m
- Heave compensated 400t
- 1x 1,390t aft and 1x 1,510t fwd carousels below deck / 3,000t carousel / multiple reels on deck
- 7.5m x 8.5m moonpool
- Accommodation for 120 persons
- 2x work-class ROVs

Fast Facts

- Moonpool positioned aft of VLS tower, allowing full access for moonpool work with cranes, winches etc
- Large back deck and underdeck carousels give ability to perform heavy construction and flex-lay scopes simultaneously (limited port calls required)
- VLS tower design along with crane capacity and access allow more scope in UTA design that can be transferred over tower



subsea 7

General Information

Classification Lloyds Register, +100A1, LI, *IWS +LMC, UMS, DP (AA), CAC(3), EP, ICC, UD strength for load of 10t/m2, Heli landing area Merwede Shipyard, Built The Netherlands 2008 Flag State Authority Isle of Man Government

Principal Dimensions

153.24m Length Overall Breadth 28.4m Depth to Maindeck 12.5m Draught (design) 7.5m Deadweight 10.130t Gross Tonnage 18.367t Net Tonnage 5,510t

Main Deck

Deck Area (aft of Moonpool) 1.750m² Deck Strength 10t/m²

Tank Capacities (100%)

2.480m³ Marine Gasoil Potable Water 655m³ **Ballast Water** 4.530m³ Anti-Heel Tanks 1,538m³ Stabiliser Tanks 716m³ Technical FW (in WB Tanks) 685m³

Power and Propulsion

Service Speed Main Engines / Generators / Propulsion

13 knots (approx)

6x 3,240kW (Diesel Electric) 3x 2,950kW stern azimuth thrusters (Wartsila) 2x 2.400kW retractable bow azimuth thrusters (Wartsila) 1x 2.200kW bow tunnel thruster (Wartsila)

DP Systems

DP Classification DP (AA) (Class II) Kongsberg Simrad SDP 22 DP System 2x Veripos DGPS Reference Systems 2x HiPap 501

1x taut wire 1x fanbeam 1x Radius system

Cranes

Huisman BV Main Deck Crane (Active heave compensation)

Main hoist 400t Whip hoist 40t

2t man-riding rating

Stbd Aft Auxiliary Deck Crane (Active heave compensation)

Main hoist 34t Whip hoist

2t man-riding rating

Stbd Midships Auxiliary Deck Crane

2t man-riding rating

Lav tower top Auxiliary Deck Crane 20t

Pipelay Systems

A vertical lay system is permanently installed for deployment of a range of flexible products. The tower consists of two aligner chutes (one port, one starboard), a retractable electric driven upper 170t tensioner and a lower retractable electric driven main 260t tensioner.

Two hold carousels with storage capacities 1,390t aft and 1,510t Fwd are provided.

A 450t and a 125t A&R winch are provided.

ROV Systems

The vessel is fitted with two over side launched work-class ROVs rated to 3,000m.

Helideck

The vessel is fitted with an approved and certified helideck suitable for Sikorsky S92 and Super Puma operations. Kongsberg HMS 100 is fitted.

Accommodation

120 persons Single cabins (with dayroom) 3 Single cabins 17 Double cabins 48 Four person cabins 1 Hospital (not included in total)

Comms Systems

The vessel is fitted with an extensive communications system including a dual KU / C band Vsat satellite communication system, 2x Inmarsat C and Inmarsat F systems.





client.enquiry@subsea7.com



www.subsea7.com



















