

VESSELS Pipelay















Vessel Info

Full specification overleaf

Seven Oceans is a pipelay vessel capable of rigid and flexible pipelay, in water depths up to 3,000m.

- Length 157m x breadth 28m
- Heave compensated 400t crane
- Main reel has storage capacity of 3,800t
- 6-inch to 16-inch diameter rigid pipeline
- Top Dynamic Tension 550*
- Accommodation for 120 persons
- 2x work-class ROVs

Fast Facts

- Capable of installing of all known flowline systems including complex Pipe-in-Pipe, Electrical Heat Traced Flowlines and Mechanically Lined Pipe
- BuBi flowlines and SCR's in 1,300m
- Global reel-lay vessel with completed projects in Europe, North America, South America, Africa and Australasia
- Proven track record operating in water depths from 19m to 2,300m
- Offshore structure lifting operations of 200t



subsea 7

General Information	
Classification Built Flag State Authority	Lloyds Register, +100A1, +LMC, UMS, DP (AA), CAC(3), EP, ICC, UD strength for load of 10+/m2, Heli landing area Merwede, Holland 2007 Isle of Man
Principal Dimensions	
Length Overall Breadth Depth to maindeck Draught design Deadweight Gross Tonnage Net Tonnage	157.3m 28.4m 12.5m 7.5m 10,930t 18,201t 5,250t
Main Deck	
Deck Area (main deck) Deck Strength Tank Capacities (100%)	650m ² 10t/m ²
Marine Gasoil Fuel Oil Potable Water Ballast Water Technical FW (in WB tank) Heeling/Stabiliser Tanks	2,800m³ 1,572m³ 655m³ 4,766m³ 600m³ 1,566m³
Power and Propulsion	
Main Engines / Generators Propulsion	6x 3,360kW (Diesel Electric) 3x 2,950kW stern azimuth thrusters 2x 2,400kW retractable bow azimuth thrusters 1x 2,200kW bow tunnel thruster
Speed / Consumptions	
Service Speed	Approximately 13 knots

DP Systems	
DP Classification DP System Reference Systems	DP (AA) - Class II Kongsberg Simrad SDP 22 3x DGPS 2x HiPAP 1x taut wire 1x fanbeam HPR interface Radius interface
Cranes	
Main Deck Crane Main Line Whipline Auxiliary Deck Crane I Auxiliary Deck Crane II Ramp Top Crane	400t 55t 40t 12t 12t

The auxiliary deck cranes are certified for man-riding operations, as is the main deck crane whipline.

Pipelaying System

The vessel is fitted with one 3,800 tonne main deck mounted reel. An optional piggy back reel can be fitted as required.

The system is suitable for products from 6-inch to 16-inches in diameter. The lay ramp system comprises of an aligner wheel, pipe straightener, 450t tensioner including dynamics (tensioner exceptional holding load of 550t including dynamics), 600t HOM clamp inc dynamics and roller box.

1x 500t and 1x 80t abandonment and recovery winches are

The operational capability of the Lay system is 550t* (*including up to 100t back tension at main reel).

ROV Systems

The vessel is fitted with two permanently installed side launching work-class Hercules ROV systems rated to 3,000 metres.

Helideck

The vessel is fitted with an approved and certified helideck. The helideck is approved for Super Puma and S92 helicopter operations. Kongsberg HMS 100 is fitted.

Accommodation

120 persons	
Captain Class Cabins	3
Officer Class Cabins (large)	3
Officer Class Cabins	
(standard)	2
Single Cabins	12
Double Cabins	48
Four-person Cabins	1
Hospital (not included in total)	1
	Captain Class Cabins Officer Class Cabins (large) Officer Class Cabins (standard) Single Cabins Double Cabins Four-person Cabins

Comms Systems

The vessel is fitted with FleetBroadband 250 and KU Band systems.





client.enquiry@subsea7.com



www.subsea7.com



















